

OFFICE OF THE MARION COUNTY SURVEYOR	
SECTION RECORD CORNER	ш
SECTION 12 TOWNSHIP 15 RANGE 4	8 1 1
DATE:	
PARTY CHIEF: Wilcoxen	-
CREW:	English Ave 500 S
TYPE OF MARKER: Harrison	
	- F F
METHOD OF ESTABLISHMENT: County: 12-14-98	
	, J
IN. S.P.C. E ZONE, NAD 83	밀
NAME: 15041204	
N: SHIIISTISHIICM)	. A
X st so	4.
[\frac{1}{2} \fra	R
5 ± 1	
Ford Plant × 6. 2 3	, A
🗴 🐧	1.
-X- X- 25.19, 25	
	2.
75.19, 03. 09.	000
\	83.81'
	Section Line 500 S
	C/L English Ave
4. 0 711	
4. 000 86.71	
899	
8	
3, (PWP)	

Original post set 1820 by John Hendricks with witnesses: 12" sugar maple S 68 W 22 links, and 14" beech N 32 E 44 links per Marion County Atlas pg. 10. Survey by 0.W. Voorhies 6-10-1868 indicates no stone but witnesses: 20" beech N 60 E 29 1/2 links, 5: beech S 60 W 1/2 link per Warren Township Legal Survey Book pg. 46. Monroe 1-27-53 called a nail over stone. Monroe 5-18-57 called a brass pin in drilled hole. MCSO 7-11-63 called a brass pin in drilled hole.McLand 5-26-70 called an iron pipe. Wilcoxen 9-9-75 called an iron pin. Jacobs 10-20-88 called an iron pin. Kiste 10-19-94 called a brass plug. Wilcoxen 12-14-98 called a brass plug. Excavated by Wilcoxen 9-17-99 and brass plug was found 5" down. Harrison set.

204	
DISTANCE	DESCRIPTION
47.48′	Cut 'x' E-end of median
83.81′	Cut 'x' S-bolt of aluminum pole base
87.68′	Mag nail w/brass washer NW PwP#345-577A 12"up
86.71′	Cut 'x' E-bolt of aluminum pole base
-75.19'	Cut 'x' E end of headwall
45.63′	Cut 'x' S-bolt of aluminum pole base
	DISTANCE 47.48' 83.81' 87.68' 86.71' -75.19'